

Data sheet

Sheet No.: TP 1.01 Rev B

Date: July 2012

TorqPlus

Performance Data Open/Close and Modulating Configurations

Available Torques, Operating Speeds, Motor Duty Cycles, Motor Voltages and Locked Rotor Amp Draws.

Torque Expression: Inch-Pounds (in-lb) and Newton Meters (Nm).

Speed Expression: Seconds per 90° output rotation.

Torque Output		Operating Speed Sec/90°	Model	Motor Duty Cycle	Locked Rotor Amp Draw					
					1 Phase /50 - 60 Hz		3Ph/60Hz		Direct Current	
in-lb	nm				115VAC	230VAC	230VAC	460VAC	12VDC	24VDC
100	11	2 <i>Note 4</i>	EM-100	30%	1.30	CF	-	-	-	-
250	28	10		30%	0.70	CF	-	-	-	-
350	39	13		30%	0.70	CF	-	-	-	-
150	17	4 <i>Note 4</i>	EM-300	30%	0.6	0.3	-	-	19.2	8.8
300	34	10		30%	0.6	0.3	-	-	19.2	8.8
400	45	15		30%	0.6	0.3	-	-	19.2	8.8
600	68	30		30%	0.6	0.3	-	-	19.2	8.8
180	20	5 <i>Note 4</i>	EM-520	30%	0.6	0.3	-	-	19.2	8.8
450	51	10		30%	0.6	0.3	-	-	19.2	8.8
600	68	15		30%	0.6	0.3	-	-	19.2	8.8
1000	113	30		30%	0.6	0.3	-	-	19.2	8.8
350	39	5 <i>Note 4</i>	EM-500	100%	0.7	0.4	-	-	8.4	7.3
700	79	10		100%	0.7	0.4	-	-	8.4	7.3
1000	113	15		100%	0.7	0.4	-	-	8.4	7.3
1600	181	30		100%	0.4	0.5	-	-	8.4	7.3
325	36	2 <i>Note 4</i>	EM-510	100%	1.6	0.8	-	-	-	18.4
600	68	5 <i>Note 4</i>		100%	1.6	0.8	-	-	-	18.4
1000	113	7 <i>Note 4</i>		100%	1.6	0.8	-	-	-	18.4
2000	226	12	EM-810	100%	3.2	1.3	CF	CF	-	-
2500	282	18		100%	.32	1.3	CF	CF	-	-
3500	395	30		100%	3.2	1.3	CF	CF	-	-
4000	452	60		100%	3.2	1.3	CF	CF	-	-
3000	339	12	EM-820	100%	3.2	1.3	CF	CF	-	-
4000	452	18		100%	3.2	1.3	CF	CF	-	-
6000	678	30		100%	3.2	1.3	CF	CF	-	-
7000	791	60		100%	3.2	1.3	CF	CF	-	-
5000	565	12	EM-830	100%	6.0	2.8	CF	CF	-	-
7000	791	18		100%	6.0	2.8	CF	CF	-	-
10000	1130	30		100%	6.0	2.8	CF	CF	-	-
10000	1130	60		100%	6.0	2.8	CF	CF	-	-
15000	1695	48	EM-840	100%	6.0	2.8	CF	CF	-	-
20000	2260	72		100%	6.0	2.8	CF	CF	-	-
300	34	10 <i>Note 4</i>	EM-SR5	100%	0.7	0.7	-	-	-	-
400	45	15		100%	0.7	0.7	-	-	-	-
600	68	30		100%	0.7	0.4	-	-	-	-
1600	181	90		100%	0.7	0.4	-	-	-	-

- NOTE: 1. Operating speed is nominal at rated torques. Final operating speed may vary depending on actual service.
 2. Actuators with 12VDC motors will have an operating speed of approximately 40% longer (slower) than that shown.
 3. CF – Consult Factory
 4. Bettis does not recommend the use of any actuator for any modulating application with an operating speed of 10 seconds or less.

BETTIS[™]

www.Bettis.com

Copyright © Emerson Process Management. The information in this document is subject to change without notice.
 Updated data sheets can be obtained from our website www.bettis.com or from your nearest Valve Automation Center.
 USA: +1 281 727 5300 Europe: +31 74 256 1010 Asia-Pacific: +65 6501 4600


EMERSON[™]
 Process Management