


## Watts Combination Units

## Features:

- 4.5 oz. bowl
- 40 micron polypropylene element
- zinc body
- maximum operating conditions:
  - temperature range: **40°F** (4.4°C) to **120°F** (48.9°C)
  - maximum operating pressure: **150 PSIG** (10.2 bar)




## Compact Polycarbonate Bowl with Metal Bowl Guard

Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
¼"	40	<b>C11-02A</b>	<b>\$507.10</b>	<b>C11-02M</b>	<b>\$444.70</b>
⅜"	60	<b>C11-03A</b>	<b>509.80</b>	<b>C11-03M</b>	<b>447.40</b>
½"	85	<b>C119-04A</b>	<b>561.25</b>	<b>C119-04M</b>	<b>498.85</b>

## Features:

- 16 oz. bowl
- 40 micron polypropylene element
- zinc body
- maximum operating conditions:
  - temperature range: **40°F** (4.4°C) to **150°F** (65.6°C)
  - maximum operating pressure: **250 PSIG** (17 bar)




## Standard Zinc Bowl with Sight Glass

Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
¾"	275	<b>C119-06AMB</b>	<b>\$1054.15</b>	<b>C119-06MMB</b>	<b>\$991.75</b>
1"	320	<b>C119-08AMB</b>	<b>1046.15</b>	<b>C119-08MMB</b>	<b>983.75</b>

## Features:

- 16 oz. bowl
- 40 micron polypropylene element
- zinc body
- maximum operating conditions:
  - temperature range: **40°F** (4.4°C) to **150°F** (65.6°C)
  - maximum operating pressure: **250 PSIG** (17 bar)



## Standard Zinc Bowl with Sight Glass

Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1½"	550	<b>C119-12AMB</b>	<b>\$1247.05</b>	<b>C119-12MMB</b>	<b>\$1184.65</b>



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 150 PSIG inlet pressure.